

REAXIS® C739W50 (EXP)

REAXIS® C739W50 is a bismuth-based catalyst used for curing a wide selection of water borne polyurethane-based formulations. **REAXIS® 739W50** exhibits a high selectivity for the NCO/OH reaction. **REAXIS® C739W50** is supplied as a 50% active catalyst in water. **REAXIS® C739W50** can be supplied in other diluents.

Technical/application information is available upon request.

Specifications

Bismuth Content (%)	18.5 – 20.5
Gardner Color Number	12 Max.
Density (g/ml @ 20°C)	1.2 – 1.5

Standard Packaging

- 44 lb (20 kg) plastic pail

General Product Characteristics

Physical State	Yellowish liquid
Solubility	Organic solvent water soluble

Storage Conditions

REAXIS® C739W50 should be stored in the original packaging. The container should be closed tightly after each use to maximize product shelf life. The material should be stored so as to prevent freezing. The material is susceptible to degradation due to light.

Reaxis Inc.
941 Robinson Highway
McDonald, PA 15057
Ph: 800-426-7273
Email: techservice@reaxis.com

Fax: 724-796-3160
Web: www.reaxis.com

This information is provided to the best of our knowledge but without obligation. Reaxis is not liable for any incorrect or missing information. This data sheet becomes invalid upon publication of a new version. Please contact us for the latest version.

Ver0812